

TASHI CHECKLIST

Before Taking Off

Preparations on the dock:

- ☐ Fill out float plan
- ☐ Shut off shore-power under dock box
- ☐ Unplug power cable

Preparations under deck:

- ☐ Check oil
- ☐ Check fuel
- ☐ Check bilge
- ☐ Check packing gland (should not drop when engine off)
- ☐ Turn on batteries and master switch
- ☐ Open sea water intake valve (sea cock)
- ☐ Check radio
- ☐ Bring winch handles & signal horn out

Preparations on deck:

- ☐ Take covers off
- ☐ Attach main halyard to headboard of mainsail
- ☐ Clear up all lines, make sure reefing lines are loose

Starting the engine:

- ☐ Make sure gear switch is in neutral and throttle slightly up
- ☐ Start engine (glow 15 sec)
- ☐ Check water flow
- ☐ Check packing gland again (should drop water 1-2 every 30 sec)

Before taking off:

- ☐ Make sure everybody has a life jacket on
- ☐ Check exit is clear of boats

After Coming Back

On deck after docking:

- ☐ Attach main halyard to topping lift
- ☐ Stow winch handles and signal horn
- ☐ Make sure outhaul is loose
- ☐ Put covers back on

Under deck:

- ☐ Turn off batteries and master switch
- ☐ Close sea water intake valve (sea cock)

On the dock:

- ☐ Connect power cable
- ☐ Spray boat
- ☐ Switch on shore-power under dock box